

Recall order is predicted by category-specific neural activity of preceding items at study

Stephanie C.Y. Chan¹, Marissa C. Applegate¹, Neal W. Morton², Sean M. Polyn², Kenneth A. Norman¹¹ Princeton University, ² Vanderbilt University


1 Introduction

Question

Do we timestamp our memories using the thoughts that are co-active at the time of encoding? Specifically, do we use the *meanings* of those thoughts to timestamp our memories?

Background

Context-based models of memory



Memories are timestamped by the concurrent state of “mental context”, which drifts slowly over time.

We use this signal to help retrieve memories. Specifically:

- When we retrieve a memory, we reinstate the mental context as-associated with that memory
- We are more likely to recall memories whose mental context is most similar to the current mental context

Consequence on recall order: We are more likely to transition between two items that were associated with similar mental contexts.


Two possibilities

What is mental context?

The semantic hypothesis: Mental context is a recency-weighted average of the meanings of our thoughts (Howard & Kahana 2002)
=> Recall transitions are more likely between items studied with similar preceding items

or

The random drift hypothesis: Mental context is a randomly-drifting signal (Estes 1955)
=> Recall transitions are more likely between items studied close in time



Approach

If we can show that semantics of prior items affect recall order, then we have provided evidence for the “semantic” hypothesis!

4 Analysis II: fMRI decoding of semantics

Prediction

We think that the category of the preceding item forms the semantic content of mental context. Because these preceding items are processed in various amounts, there will be some naturally-occurring variance in the semantic similarity of context for Evel Knievel pairs.

Prediction: Evel Knievels are most likely to occur if the preceding items were both highly activated in the brain.

So, we use the following similarity score, and divide the transitions into two bins:

Similarity score =		Activation of preceding category for 1st item	x	Activation of preceding category for 2nd item
high similarity	= {	high	x	high
low similarity	= {	low	x	high
		high	x	high
		low	x	low

5 Analysis III: Model-fitting

Motivation & Approach

We need a principled way to discern contributions of semantic and temporal effects to recall order => a model!

Prediction: A context model that incorporates semantics will do better at predicting recall order than a model that does not.


Model description

Overview

The model accepts studylists as input.
It estimates drift in mental context, and also makes predictions of recall order.

Context drift at study


Context drifts according to the items that were studied. Item memories are linked to this drifting context.



Context drift at recall

Drifts according to the items that were studied, and also the retrieved context.

Recalled items:



Two kinds of context (at study and recall)

The **semantic context** drifts according to the categories of the item.

The **temporal context** treats each item as orthogonal, and therefore does not contain any semantic information.

Recall predictions

contextual affinity for item N = similarity (context at study of item N , current context)

$$\text{Probability of recall (item } N) = wS \times \left(\begin{matrix} \text{semantic} \\ \text{contextual affinity} \end{matrix} \right) + (1 - wS) \times \left(\begin{matrix} \text{temporal} \\ \text{contextual affinity} \end{matrix} \right)$$

6 Conclusions


Recall order seems to be affected by **the semantic content of the items studied immediately before** each recalled items. This is congruent with the theory that our memories are timestamped by the thoughts that are co-active at the time of the memory, and that we use these timestamps to help us retrieve our memories.

- I - During recall, subjects were relatively more likely to transition between items preceded by the same semantic category (vs. items preceded by different categories).
- II - During recall, subjects were more likely to transition between pairs of items preceded by more similar semantics, as estimated by an fMRI brain decoder.
- III - Model-fitting will soon be applied to real data.


Method

Multivariate pattern analysis (MVPA)

We estimate the activation level of preceding items by applying a brain decoder to the fMRI data from study.



Results




fMRI activation of preceding items at study predicts transition likelihood at recall ($p = 0.06$, $n = 17$)


Results on simulated data

Simulations were made by varying the amount of semantics contribution to mental context, by varying wS from 0 (no semantics) to 1 (maximal semantics).

Model performance: How well does the model predict the simulated recalls?



Model comparison



wS_{fixed0} performs better than wS_{fitted} **only** when wS is actually 0!

This indicates that we can use this measure to determine whether or wS in our real data is greater than 0.

Acknowledgements

This research was supported by the NSF/NIH Collaborative Research in Computational Neuroscience Program, grant # NSF IIS-1009542.

Citations

Estes, W.K. 1955. Statistical theory of spontaneous recovery and regression. Psychol. Rev. 62: 145-154.
MW Howard, MJ Kahana (2002). A distributed representation of temporal context. J Math Psych 46: 269-299.